

**Product Datasheet model i-3 9190 275**

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Innovative protective spectacle, perfectly fit the face</li><li>* Individually adjustable side arms with variable inclination</li><li>* Integrated Softflex zone ensures outstanding wearer comfort for all head sizes</li><li>* Softflex nose piece with flexible adjustment ensures comfortable, pressure-free fit and remain firmly in place</li><li>* Soft ear and Softflex bridge pieces ensure a secure fit in any situation</li></ul>
<b>Technical details</b>	
<b>Frame</b>	<b>Front piece/Temple</b>
Material	TPU/TPE
Features	variable inclination, individually adjustable
Colour	anthracite-blue

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
No. of certificat. body	0196
<b>Lens</b>	
Material	PC
Thickness	2,2 mm
Coating	uvex supravision excellence
Colour	clear
<b>Marking</b>	
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

**Miscellaneous**

Weight

Packing

Standards

30 g

5 spectacles per box

160 spectacles per cardboard box

DIN EN 166 + DIN EN 170