

# uvex

**SAFETY  
EYEWEAR**

21.09.2015  
SBU-E-PGM-PM

## Product Datasheet model pheos 9192 225



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Modern fashion-look</li><li>* Duo spherical lens provides excellent all round vision</li><li>* Eye plus-protection protects the eyebrows through an additional chamfer at the upper range</li><li>* A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps</li><li>* Outstanding ventilation ensures a well eye climate</li><li>* Temple ends with non-slip components</li></ul>
<b>Technical details</b>  <b>Frame</b>  Material Features Colour	<b>Front piece/Temple</b> POM/TPE excellent ventilation black-green

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	supravison excellence
Colour	clear
<b>Filter</b>	
Manufacturer's ID code	<b>Marking</b> 2C-1,2 ( DIN EN 170)
Optical class	W 1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	30 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170